

# ZAYER

## MEMPHIS 6000 (N° 68.039)



龙门数控铣床或加工中心·移动桥带固定工作台及横梁  
Gantry type machining center, moving bridge with fixed table and cross beam.

规格

### TECHNICAL SPECIFICATIONS

纵向行程 Longitudinal travel	mm	6000
横向行程 Cross travel	mm	3000
垂直向行程 Vertical travel	mm	1250
工作台面 Table surface	mm	5500 x 3000
立柱间距离 Distance between columns	mm	4000
从工作台到 30° 铣头主轴鼻端最大距离 Max. distance from table to spindle nose of 30° head	mm	1465
从工作台到带电主轴的 30° 铣头主轴鼻端的最大距离 Max. distance from table to spindle nose of 30° head with electrospindle)	mm	1355
工作进给 Working feed	mm/min	达到/ up to 20000
快速进给 Rapid feed	mm/min	50000
铣头 Head		30° 连续旋转 30° continuous rotation 30° 带电主轴 30° with electrospindle
功率 Power	kW	43 (30°全轴头 / 30° head) 23 (30° 带电主轴的铣头/ 30° with electrospindle)
主轴头速度 Speed of the spindle head	min <sup>-1</sup>	6000 (30°全轴头 / 30° head) 24000 (30° 带电主轴的铣头/ 30° with electrospindle)
刀库 Tool magazine		40
冷却设备 Coolant equipment		6-37 的两个泵以及 5bar, 1000l 容量 Two pumps of 6-37 and 5 bar, 1000 l
排屑器 Chip conveyer		2 个纵向鹅颈式+1 个横向鹅颈式 2 longitudinal + 1 cross goose neck
CNC 数控系统		海德汉 iTNC 530 HSCI Heidenhain iTNC 530 HSCI