



Product information:

AETOS

GANTRY

SPECIFICATIONS

	AETOS
Table length - mm	2.500 - 3.500 - 4.500 ...
Table width - mm	2.000 (2.500 - 3.000 - 3.500 - 4.000)*
Distance between columns - mm	3.200 (3.700 - 4.200 - 4.700 - 5.200)*
Longitudinal travel - mm	3.000 - 4.000 - 5.000 ...
Cross travel - mm	2.000 (2.500 - 3.000 - 3.500 - 4.000)*
Vertical travel - mm	1.200 (1.500)*
Max. distance from table to spindle nose - mm	1.440 (high torque) / 1.550 (high speed)
Rapid feed - mm/min	up to 50.000
Working Feed - mm/min	up to 45.000
Drives:	
. Longitudinal axis	ball screw rack and double motor and pinion (longitudinal >=5000)?5000)
. Cross axis	ball screw
. Vertical axis	ball screw
Power - kW	30 (43)* (high torque) / 33 (high speed)
Speed of the spindle head - min-1	6.000 (high torque) / 18.000 (high speed)
Accuracies acc. to ISO 230-2: 2006 Annex B Step cycle:	
. Positioning accuracy - mm	0,008/4000
. Repeatability accuracy - mm	0,005/4000
Tool magazine	30 (20-40-60)*
Allowed weight on the table - kg/m ²	15.000

(Optional) *

ACCESSORIES


	AETOS
HEADS	
HEADS (High torque):	
45° head, 360x1° and 360x1°	•
Compatible heads:	
30° head, positioning / continuous rotation	○

AETOS

45° head 360.000 positions, 0,001° / continuous rotation	<input type="radio"/>
Direct Outlet head	<input type="radio"/>
HEADS (High speed):	
Other possible heads:	
40° head with electrospindle, 42 kW, 15000 rpm	<input type="radio"/>
Chip Conveyor	<input type="checkbox"/>
Coolant tank 22 + 5 bar	<input type="checkbox"/>

Standard Optional No available

PRODUCT IMAGES



HEAD IMAGES



45° head, 360x1° and 360x1°



40° head with electrospindle, 42 kW, 15000 rpm



45° automatic head 360.000 positions, 0,001°



Direct Outlet head



30° automatic head 360.000 pos. 0,001°

RELATED APPLICATIONS

Más información en www.zayer.com